

#### Mission Profile

Fast Roping 2 ropes simultaneously
Rappelling 4 ropes simultaneously

Rescue and Evacuation fixed and variable rope technique

External load HEC, NHEC

#### **Features**

- Two self-securing couplings on each side
- Redundant, safe load release system
- Reliable and repeatable electric geardrive release system no pyrotechnics, no solenoids
- Retracted position for rappelling and external load ops
- Extended position with increased skid clearance for fast roping ops

### Configuration Options

- L/H and R/H installation
- Mechanical and electrical load release system
- Harness securing hardpoints
- Exit handle

#### Facts and Numbers

Installation mass: 14.0 kg to 20.2 kg each side

Load capacity: 180 kg per coupling 620 kg max.total

Coupling spacing: 850 mm

Skid clearance: 200 mm extended Installation time: < 2 min 2 persons

Designed as a successor to the hugely successful EAD01 external load system (operating in 200+ numbers worldwide), the new EAD03 system combines the proven safety, intuitive handling and efficiency of its predecessor with a number of improvements. It is lighter, stronger, more streamlined and features a unique active drive release system with double redundancy for guaranteed release in an emergency and fourfold redundancy against unintentional loss of load.

Operational convenience is improved by adding external attachment lugs for harnesses, an exit handle and new controls for the retraction mechanism. **STC approval on EC145/H145** 





# Contact ecms Aviation Systems GmbH Hirschmann-Ring 28 71726 Benningen, Germany info@ecms-gmbh.de www.ecms-gmbh.de

## Product Facts EAD03 System

